

AFRRI TN68-3
FEBRUARY 1968

AFRRI
TECHNICAL
NOTE

NUMIT-ONE AMENDMENT #2
(FOR THE SDS 920)

AFRRI TN68-3

ARMED FORCES RADIOBIOLOGY RESEARCH INSTITUTE
Defense Atomic Support Agency
Bethesda, Maryland


Distribution of this document is unlimited.

This report has been approved for open publication by the Department of Defense

NUMIT-ONE AMENDMENT #2

(FOR THE SDS 920)

R. W. ROCKWELL



R. E. CARTER
Chairman
Physical Sciences Department



HUGH B. MITCHELL
Colonel, USAF, MC
Director

ARMED FORCES RADIOBIOLOGY RESEARCH INSTITUTE
Defense Atomic Support Agency
Bethesda, Maryland

Distribution of this document is unlimited

TABLE OF CONTENTS

	Page
Foreword (Nontechnical summary)	iii
Abstract	iv
I. Introduction	1
II. Accuracy	1
III. Input Limitations	2
IV. Input and Output Formats	3
V. Operation	4
References	5
Appendix A	7
Appendix B	9
Figure 1	10

FOREWORD
(Nontechnical summary)

This report describes a numerical integration program much like the amended form of NUMIT-ONE but written for the SDS 920, a faster and larger computer. While the flow chart is identical to the amended version of NUMIT-ONE, the coding has taken advantage of the more flexible SDS FORTRAN II and the input and output devices have been changed to paper tape since this is standard equipment for SDS 900 series computers and a card read-punch is not available for our SDS 920.

ABSTRACT

An amendment to NUMIT-ONE is presented. The program utilizes Simpson's Rule to perform integration over any closed intervals on the SDS 920.

I. INTRODUCTION

NUMIT-ONE, originally coded for the IBM 1620, has now been recoded for the SDS 920. The code follows the flow chart given in the NUMIT-ONE amendment.^{1, 2} The code itself approximately duplicates the IBM 1620 code; the only changes being those to take advantage of SDS FORTRAN II and input/output instructions. Familiarity with both of the previous publications is assumed.

Equipment needed:

FORTRAN II Processor

SDS 920 with minimum 4 K memory

While it has not been attempted, this program could probably be compiled and run on a smaller SDS computer of the 900 series.

II. ACCURACY

Floating point quantities in the 920 are held to approximately 12 digits unlike the IBM 1620 where variable precision parameters are possible. Generally, one can obtain six significant figures, the maximum output precision now called for.

Proper analysis prior to attempting to integrate, e.g., plotting data to visually select subintervals of integration, will have the double benefit of improving accuracy and reducing machine time. The test case in Appendix B illustrates this. On the first run the total interval was broken into three parts, with each subinterval carefully chosen so that unnecessary extremes would not be reached in any interval and the results for the parts were summed after the three passes. The result is an answer accurate to approximately six significant figures in a few minutes of machine time.

One can integrate over the entire interval in cases when time for analysis is short; that is, when plotting and other manual analysis is not possible. However, the second run of the test case in Appendix B using the entire interval method took over twice as much machine time and the result was slightly less accurate than the previous run after 14 iterations. Analysis is important when time permits.

A word of caution about the limits of integration: a situation in which the program will break down occurs when integrating over an interval where the integrand takes on both positive and negative values and produces an integral close to zero. In such cases, significant figures will be lost during integrating and DELTA J will exhibit a wild behavior instead of converging rapidly as it should. In a case like this, it is best to split the integrand into at least two parts, each containing a nonzero part of the total integral.

III. INPUT LIMITATIONS

Input limitations are the same as for the amended NUMIT-ONE for the IBM 1620 with one exception. J_{\max} for this version must not be more than 24 due to limits on the size of fixed point quantities in SDS FORTRAN II. Generally this allows for more iterations than one would be willing to use.

The integrand, $f(x)$, is provided by a subprogram of the FUNCTION type called FUN (X,N). X, computed in the main program, is the value of X when the function is called on; N* is the 'pass number'. FUN must appear on the left of an arithmetic statement equivalent to the integrand in the subprogram before returning to the main program.

* The integral is evaluated over several separate X regions as a sum of several independent integrals over disjoint regions; the integer variable describing the separate integrals is N.

IV. INPUT AND OUTPUT FORMATS

Input Format

Input is by paper tape. The following quantities are specified in the input (floating point quantities are in lower case, fixed point quantities in upper case).

a = lower limit of interval

b = upper limit of interval

J_{max} = maximum number of iterations desired

Δ = convergence criterion (floating point)

Line 1

Alpha Identification. Reproduced in the output and does not affect processing. Up to 80 characters permitted.

Line 2

Integrand Specification. Contains alphanumeric information to identify integrand in output. This does not affect processing. Up to 48 characters permitted.

Line 3

		<u>Format</u>
Columns 1-11	a	E 11.6
Columns 12-22	b	E 11.6
Columns 23-25	J _{max}	I 3
Columns 26-33	Δ	F 8.6
Columns 34-35	Switch	F 2.0

Following line 3 may be any number of additional lines with new values of a, b, J_{max}, and Δ punched according to the same formats. If more lines follow, switch must be punched. If no lines follow, switch should not be punched. In the last line, switch must not be punched.

Errors in Input

All the error checks listed in AFRRI SR65-1 are made, with one change. J_{\max} is permitted to be as high as 24 instead of 11 before an error message will be punched and the computer halts.

Output Format

Output is identical to the amended form of NUMIT-ONE for the IBM 1620, the only change being that output is on paper tape rather than cards.

Two sample listings are in Appendix B.

V. OPERATION

Operation is routine. The standard FORTRAN II compiler is used and no switches are utilized.

REFERENCES

1. Rockwell, R. W. and Garrett, C. W. NUMIT-ONE; a numerical integration program in one-dimension for the IBM 1620 Computer. Bethesda, Maryland, Armed Forces Radiobiology Research Institute Scientific Report SR65-1, 1965.
2. Rockwell, R. W. NUMIT-ONE Amendment #1. Bethesda, Maryland, Armed Forces Radiobiology Research Institute Technical Note TN68-1, 1968 (in press).

APPENDIX A

Source Program

```

= 1 C NUMIT ONE - ROCKWELL - NOV, 1965
= 2 DIMENSION F[0/2],P[0/2],Q[0/2],U[6]
= 3 P[0]=1.
= 4 P[1]=4.
= 5 P[2]=1.
= 6 Q[0]=1.
= 7 Q[1]=2.
= 8 Q[2]=1.
= 9 N=0
= 10 TOTAL = 0.
= 11 ACCEPT TAPE 100
= 12 PUNCH TAPE 100
= 13 PUNCH TAPE 101
= 14 ACCEPT TAPE 107, [U[i],i=1,6]
= 15 PUNCH TAPE 108, [U[i],i=1,6]
= 16 1 ACCEPT TAPE 102,A,B,JMAX,DELTA1,SW1
= 17 IF[IF[A,B]]3,2,3
= 18 2 PUNCH TAPE 103
= 19 STOP
= 20 3 IF[DELTA1]5,4,5
= 21 4 PUNCH TAPE 104
= 22 STOP
= 23 5 IF[JMAX-24]7,7,6
= 24 6 PUNCH TAPE 105
= 25 STOP
= 26 7 IF[JMAX-2]6,8,8
= 27 8 SUM1=0.
= 28 SUM=0.
= 29 N=N+1
= 30 J=1
= 31 K2=2
= 32 PUNCH TAPE 106,B,JMAX,A,DELTA1
= 33 9 DELX=[B-A]/[2,**J]
= 34 IF[J-1]10,10,14
= 35 10 DO 11 I=0,2
= 36 X=A+I*DELX
= 37 F[I]=FUN[X,N]
= 38 SUM1=SUM1+Q[I]*F[I]
= 39 11 SUM =SUM + P[I]*F[I]
= 40 AN1=DELX*SUM/3.
= 41 J=J+1
= 42 GO TO 9
= 43 14 SUM=0.
= 44 DO 15 I=1,K2
= 45 X=A+[2*I-1]*DELX
= 46 15 SUM = SUM+FUN[X,N]
= 47 AN2 = DELX*[4.*SUM+SUM1]/3.
= 48 DELTA = ABSF[[(AN1-AN2)/AN2*100.]]
= 49 IF[DELTA-DELTA1]19,19,16
= 50 16 IF[J-JMAX]17,19,19
= 51 17 AN1=AN2
= 52 SUM1= SUM1+2.*SUM
= 53 PUNCH TAPE 109,J,AN2,DELTA
= 54 J=J+1
= 55 K2=2*K2

```

```

= 56      GO TO 9
= 57      19 PUNCH TAPE 110,J,N,AN2,DELTA
= 58      TOTAL=TOTAL+AN2
= 59      IF(SW1)1,20,1
= 60      20 PUNCH TAPE 111,N,TOTAL
= 61      STOP
= 62      100 FORMAT(80H
= 63      1
= 64      107 FORMAT(6A8]
= 65      108 FORMAT(15X,$F[X] = $,6A8]
= 66      101 FORMAT(/15X,$NUMIT ONE [ONE-DIM. INTEGRATION, SIMPSONS RULE]$]
= 67      102 FORMAT(2E11.6,13,F8.6,F2.0]
= 68      103 FORMAT(10X,$CHECK INPUT - A=B$]
= 69      104 FORMAT(10X,$CHECK INPUT - DELTA = 0$]
= 70      105 FORMAT(10X,$CHECK INPUT - JMAX OUTSIDE RANGE$ ]
= 71      106 FORMAT(/35X,$INPUT DATA$/21X,$B = $1PE12.5,9X,$J[ MAX] = $13/
= 72      121X,$A = $1PE12.5,9X,$DELTA1 = $1PE10.4//16X,$ITEPATION$,11X,
= 73      2$INTEGRAL$,13X,$DELTA$]
= 74      109 FORMAT(18X,13,12X,1PE12.5,8X,0PF10.4]
= 75      110 FORMAT(18X,13,$[PASS$,12,$1$,4X,1PE12.5,8X,0PF10.4///]
= 76      111 FORMAT(32X$NO. PASSES = $13/29X$TOTAL INTEGRAL= $1PE12.5/
= 77      139X$END$]
= 78      END

```

PROGRAM ALLOCATION

00007 F	00015 P	00023 Q	00031 U
00045 N	00046 I	00047 JMAX	00050 J
00051 K2	00052 TOTAL	00054 A	00056 B
00060 DELTA1	00062 SW1	00064 SUM1	00066 SUM
00070 DELX	00072 X	00074 AN1	00076 AN2
00100 DELTA			

SUBPROGRAMS REQUIRED

IF FUN ABSF

THE END

APPENDIX B

Test Case

Running time is still highly variable and depends strongly on the integrand. However, time is much shorter than on the IBM 1620. No case is known which is not at least 15 times as fast on the SDS 920 as on the other computer, the ratio being highest when the number of iterations is large. The formula given in the previous reports,

$$t = K \cdot 2^{J_{act}}$$

where K is a constant dependent on the integrand, still appears to be valid when the number of iterations is large enough so the time spent computing is large compared to the time spent punching tape.

The function illustrated here,

$$f(x) = x^7 \frac{\sqrt{1-x^2}}{(2-x)^{13/2}}$$

has been the most difficult tested thus far. It converges slower and the value of K (7.47×10^{-4} sec) is larger than any heretofore reported. Figure 1 illustrates the function over the intervals of -1 to 1. Running time for RUN 1 was 5.5 minutes; RUN 2 took 12.25 minutes.




Figure 1

```

C      SOURCE STATEMENTS OF SUBROUTINE
C
      FUNCTION FUN(X,N)
      FUN=X**7*SQRTF(1.-X*X)/(2.-X)**6.5
      RETURN
      END

```

INPUT DATA

RUN 1

```

      X**7*SQRT(1-X*X)/(2-X)**13/2      TEST FUNCTION
-1000000+01,+500000+00,12,.010000,1,
+500000+00,+800000+00,12,.001000,1,
+800000+00,+100000+01,12,.000100,

```

RUN 2

```

      X**7*SQRT(1-X*X)/(2-X)**13/2      TEST FUNCTION
-1000000+01,+100000+01,14,.000500,

```


OUTPUT DATA

RUN 1

TEST FUNCTION

NUMIT ONE [ONE-DIM. INTEGRATION, SIMPSONS RULE]
 $F[X] = X^{**7} * \text{SQRT}(1-X*X)/(2-X)^{**13/2}$

INPUT DATA

B = 5.000000E-01 J[Max] = 12
A = -1.000000E 00 DELTA1 = 9.9999E-03

ITERATION	INTEGRAL	DELTA
2	3.31206E-05	265.1566
3	-1.74285E-05	290.0372
4	-3.03975E-05	42.6647
5	-3.29935E-05	7.8681
6	-3.36745E-05	2.0223
7	-3.38945E-05	0.6491
8	-3.39703E-05	0.2231
9	-3.39968E-05	0.0781
10	-3.40062E-05	0.0275
11[PASS 1]	-3.40095E-05	0.0097

INPUT DATA

B = 7.99999E-01 J[Max] = 12
A = 5.00000E-01 DELTA1 = 9.9999E-04

ITERATION	INTEGRAL	DELTA
2	2.90366E-03	3.5586
3	2.89730E-03	0.2193
4	2.89694E-03	0.0126
5[PASS 2]	2.89692E-03	0.0008

INPUT DATA

B = 1.00000E 00 J[Max] = 12
A = 7.99999E-01 DELTA1 = 9.9999E-05

ITERATION	INTEGRAL	DELTA
2	1.95064E-02	16.7288
3	2.05071E-02	4.8794
4	2.08279E-02	1.5404
5	2.09361E-02	0.5167
6	2.09735E-02	0.1784
7	2.09866E-02	0.0624
8	2.09912E-02	0.0219
9	2.09928E-02	0.0077
10	2.09934E-02	0.0027
11	2.09936E-02	0.0010
12[PASS 3]	2.09936E-02	0.0003

NO. PASSES = 3
TOTAL INTEGRAL= 2.38566E-02
END

RUN 2

TEST FUNCTION

NUMIT ONE [ONE-DIM, INTEGRATION, SIMPSONS RULE]
 $F[X] = X^{**7} * \text{SQRT}(1 - X * X) / (2 - X)^{**13/2}$

INPUT DATA

B = 1.00000E 00 J[MAX] = 14
A = -1.00000E 00 DELTA1 = 4.9999E-04

ITERATION	INTEGRAL	DELTA
2	3.11637E-04	100.0000
3	6.93780E-03	95.5081
4	1.70652E-02	59.3454
5	2.17058E-02	21.3795
6	2.31639E-02	6.2948
7	2.36230E-02	1.9433
8	2.37758E-02	0.6426
9	2.38283E-02	0.2204
10	2.38466E-02	0.0769
11	2.38531E-02	0.0270
12	2.38554E-02	0.0095
13	2.38562E-02	0.0034
14[PASS 1]	2.38564E-02	0.0012

NO. PASSES = 1
TOTAL INTEGRAL= 2.38564E-02
END

DISTRIBUTION LIST

AIR FORCE

Office of the Surgeon General, Department of the Air Force, Headquarters U. S. Air Force, Washington, D. C. 20333 (1)
Air Force Institute of Technology, Air University, USAF, Wright-Patterson Air Force Base, Ohio 45433 (1)

ARMY

The Surgeon General, Department of the Army, Washington, D. C. 20315 (1)
Director, Walter Reed Army Institute of Research, Washington, D. C. 20012 (1)
Chief of Research and Development, Department of the Army, Washington, D. C. 20310, ATTN: Nuclear, Chemical and Biological Division (1)
Commanding Officer, U. S. Army Nuclear Defense Laboratory, Edgewood Arsenal, Maryland 21040 (1)

NAVY

Chief, Bureau of Medicine and Surgery, Department of the Navy, Washington, D. C. 20390 (1)
Chief of Naval Research, Department of the Navy, Washington, D. C. 20390 (1)
Director, U. S. Naval Research Laboratory, Washington, D. C. 20390 (1)
Commanding Officer and Director, U. S. Naval Radiological Defense Laboratory, San Francisco, California 94135 (1)
Chief of Naval Operations, Department of the Navy, Washington, D. C. 20350, ATTN: Director, Atomic Energy Division (1)
Commanding Officer, U. S. Naval Hospital, NNMCC, Bethesda, Maryland 20014, ATTN: Director, REEL (1)

D. O. D.

Director, Defense Atomic Support Agency, Washington, D. C. 20305 (1)
Director, Defense Atomic Support Agency, Washington, D. C. 20305, ATTN: DDST (1)
Director, Defense Atomic Support Agency, Washington, D. C. 20305, ATTN: Chief, Radiation Directorate (1)
Director, Defense Atomic Support Agency, Washington, D. C. 20305, ATTN: Medical Directorate (4)
Director, Defense Atomic Support Agency, Washington, D. C. 20305, ATTN: Technical Library (2)
Commander, Field Command, Defense Atomic Support Agency, Sandia Base, Albuquerque, New Mexico 87115 (1)
Defense Documentation Center, Cameron Station, Alexandria, Virginia 22314 (20)

OTHER GOVERNMENT

U. S. Atomic Energy Commission, Washington, D. C. 20545 (1)
U. S. Atomic Energy Commission, Division of Peaceful Nuclear Explosives, Washington, D. C. 20545 (1)
National Library of Medicine, Bethesda, Maryland 20014 (1)

OTHER

Scientific Committee on the Effects of Atomic Radiation, United Nations, Room 3267, New York, N. Y. 10017 (1)
Argonne National Laboratory, 9700 South Cass Avenue, Argonne, Illinois 60440 (1)
Los Alamos Scientific Laboratory, Los Alamos, New Mexico 87544 (1)
Oak Ridge Institute of Nuclear Studies, Oak Ridge, Tennessee 37831 (1)
Lawrence Radiation Laboratory, University of California, Livermore, California 94551 (1)
Brookhaven National Laboratory, Upton, Long Island, New York 11973 (1)
Director of Research, Lovelace Foundation, 4800 Gibson Boulevard, Albuquerque, New Mexico 87108 (1)
1620 Users Group Newsletter, Computer Center, Georgia State College, 33 Gilmer Street, Atlanta, Georgia 30303
ATTN: Professor W. H. Wells (1)

UNCLASSIFIED

Security Classification

DOCUMENT CONTROL DATA - R&D

(Security classification of title, body of abstract and indexing annotation must be entered when the overall report is classified)

1. ORIGINATING ACTIVITY (Corporate author) Armed Forces Radiobiology Research Institute Defense Atomic Support Agency Bethesda, Maryland 20014		2 a. REPORT SECURITY CLASSIFICATION UNCLASSIFIED	
		2 b. GROUP N/A	
3. REPORT TITLE NUMIT-ONE AMENDMENT #2 (FOR THE SDS 920)			
4. DESCRIPTIVE NOTES (Type of report and inclusive dates)			
5. AUTHOR(S) (Last name, first name, initial) Rockwell, R. W.			
6. REPORT DATE February 1968		7 a. TOTAL NO. OF PAGES 16	7 b. NO. OF REFS 2
8 a. CONTRACT OR GRANT NO.		9 a. ORIGINATOR'S REPORT NUMBER(S) AFRRI TN68-3	
b. PROJECT NO.			
c. R MD 4 908		9 b. OTHER REPORT NO(S) (Any other numbers that may be assigned this report)	
d.			
10. AVAILABILITY/LIMITATION NOTICES Distribution of this document is unlimited			
11. SUPPLEMENTARY NOTES		12. SPONSORING MILITARY ACTIVITY Defense Atomic Support Agency Washington, D. C. 20305	
13. ABSTRACT An amendment to NUMIT-ONE is presented. The program utilizes Simpson's Rule to perform integration over any closed intervals on the SDS 920.			

14. KEY WORDS	LINK A		LINK B		LINK C	
	ROLE	WT	ROLE	WT	ROLE	WT

INSTRUCTIONS

1. **ORIGINATING ACTIVITY:** Enter the name and address of the contractor, subcontractor, grantee, Department of Defense activity or other organization (*corporate author*) issuing the report.

2a. **REPORT SECURITY CLASSIFICATION:** Enter the overall security classification of the report. Indicate whether "Restricted Data" is included. Marking is to be in accordance with appropriate security regulations.

2b. **GROUP:** Automatic downgrading is specified in DoD Directive 5200.10 and Armed Forces Industrial Manual. Enter the group number. Also, when applicable, show that optional markings have been used for Group 3 and Group 4 as authorized.

3. **REPORT TITLE:** Enter the complete report title in all capital letters. Titles in all cases should be unclassified. If a meaningful title cannot be selected without classification, show title classification in all capitals in parentheses immediately following the title.

4. **DESCRIPTIVE NOTES:** If appropriate, enter the type of report, e.g., Interim, progress, summary, annual, or final. Give the inclusive dates when a specific reporting period is covered.

5. **AUTHOR(S):** Enter the name(s) of author(s) as shown on or in the report. Enter last name, first name, middle initial. If military, show rank and branch of service. The name of the principal author is an absolute minimum requirement.

6. **REPORT DATE:** Enter the date of the report as day, month, year, or month, year. If more than one date appears on the report, use date of publication.

7a. **TOTAL NUMBER OF PAGES:** The total page count should follow normal pagination procedures, i.e., enter the number of pages containing information.

7b. **NUMBER OF REFERENCES:** Enter the total number of references cited in the report.

8a. **CONTRACT OR GRANT NUMBER:** If appropriate, enter the applicable number of the contract or grant under which the report was written.

8b, 8c, & 8d. **PROJECT NUMBER:** Enter the appropriate military department identification, such as project number, subproject number, system numbers, task number, etc.

9a. **ORIGINATOR'S REPORT NUMBER(S):** Enter the official report number by which the document will be identified and controlled by the originating activity. This number must be unique to this report.

9b. **OTHER REPORT NUMBER(S):** If the report has been assigned any other report numbers (*either by the originator or by the sponsor*), also enter this number(s).

10. **AVAILABILITY/LIMITATION NOTICES:** Enter any limitations on further dissemination of the report, other than those imposed by security classification, using standard statements such as:

- (1) "Qualified requesters may obtain copies of this report from DDC."
- (2) "Foreign announcement and dissemination of this report by DDC is not authorized."
- (3) "U. S. Government agencies may obtain copies of this report directly from DDC. Other qualified DDC users shall request through _____."
- (4) "U. S. military agencies may obtain copies of this report directly from DDC. Other qualified users shall request through _____."
- (5) "All distribution of this report is controlled. Qualified DDC users shall request through _____."

If the report has been furnished to the Office of Technical Services, Department of Commerce, for sale to the public, indicate this fact and enter the price, if known.

11. **SUPPLEMENTARY NOTES:** Use for additional explanatory notes.

12. **SPONSORING MILITARY ACTIVITY:** Enter the name of the departmental project office or laboratory sponsoring (paying for) the research and development. Include address.

13. **ABSTRACT:** Enter an abstract giving a brief and factual summary of the document indicative of the report, even though it may also appear elsewhere in the body of the technical report. If additional space is required, a continuation sheet shall be attached.

It is highly desirable that the abstract of classified reports be unclassified. Each paragraph of the abstract shall end with an indication of the military security classification of the information in the paragraph, represented as (TS), (S), (C), or (U).

There is no limitation on the length of the abstract. However, the suggested length is from 150 to 225 words.

14. **KEY WORDS:** Key words are technically meaningful terms or short phrases that characterize a report and may be used as index entries for cataloging the report. Key words must be selected so that no security classification is required. Identifiers, such as equipment model designation, trade name, military project code name, geographic location, may be used as key words but will be followed by an indication of technical context. The assignment of links, rules, and weights is optional.